

Battery chargers: T24808B

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

T24808B



24V 8A battery charger processor controlled , with step down characteristics

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

T24V 8 A Battery Charger

Technical Parameters:

- nominal input voltage: 230V AC, 50Hz , 1.4A
- nominal charging voltage: 24 V DC
- max. charging current: 8 A DC
- max. output voltage:
- max. consumption from battery: 8mA
- ambient temperature: -10 -50°C
- operational temperature: max.60°C
- charging characteristics: Step down 8A - 4A - 2A this is a , special , very safe characteristic
- size: 115*160*57mm

Battery chargers: T24808B

- weight: 1,4 kg
- IP class: 44
- Protected against reverse polarity and short circuit.
- Equipped with an additional protection circuit against output overvoltage.