

Battery chargers: T2414B

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

T2414B



24V 20A battery charger processor controlled

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

T2414B Battery Charger

The charger is suitable for special charging of 24V, 20-230Ah batteries.

Technical specifications:

- Nominal input voltage: 230V AC, 50Hz/2.7A
- Nominal charging voltage: 24V DC
- Maximal charging current: 14A DC
- Max output voltage: 28,8V / 29,6V (adjustable)
- Ambient temperature: -30°C – +60°C
- Operation temperature: 24-50°C
- Size: 260*158*60mm
- Weight: 2,2 Kg
- IP class: 40
- Equipped with an additional protection circuit against output overvoltage.

