

Battery testers: Tester 24V 100A

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Warning: file_put_contents(/260916.ini): failed to open stream: Permission denied in /home/forexkft/public_html/en.forex.hu/libraries/joomla/filesystem/file.php on line 440

Tester 24V 100A



Forex Battery Tester USB TE 24100 USB 24V 1-100A software+cable

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

General Description:

This tester is used for measuring the capacity of 24V battery blocks.
It can also be used for testing 24V generators.

Technical Parameters:

- Discharging currents: 1A-20A with 1A steps, 20A – 100A with 5A steps
- Current stability: better than 2% or + 0.2A
- Cut off voltage: 1.0 V/cell – 1.95V/cell with 0.05V/cell steps
- 15V – 18V és 27,6V-32V 10% current accuracy

Battery testers: Tester 24V 100A

- Switch off voltage: 15V – 22,8 V (in 0.6 A steps)
- Voltage measure: between 15V – 32V
- Accuracy : better than 1% (if the voltage is over 16.8V) Below 16.8V the current error changes according to the voltage.
- Discharging time: 1-20 hours with 1 hour step, or infinite time
- Sampling time : 0,1 – 240 sec
- Discharged Ah measurement: 0,1 – 1000 Ah, 0,4% accuracy
- Number of possible measures: 15
- Parallel connection: max. 4 testers at a time (parallelling unit is an option)
- Dimensions: 260 x 220 x 270 mm

[Data sheet \(pdf\)](#) (old one)

[Data sheet, manual \(Sw6 -\)](#)